

## safety data sheet

## to product

## Gloss and hardening agent for plasters

## 1. Identification of the substance / preparation and company

## **Emergency number:**

Tox Info Suisse, Freiestrasse 16, 8032 Zürich; Tox-Info Suisse: 145 (24h-operation); info@toxinfo.ch; **In case of emergency: Tel. 145**; (abroad: +41 44 251 51 51); information: +41 44 251 66 66

## **Company name:**

abcdental <sup>o</sup>	abc dental ag	Gaswerkstrasse 6, 8952 Schlieren Tel. 044 755 51 00, Fax 044 755 51 01
C NDOR  A MHENRY SCHEIN" COMPANY	Condor Dental Research CO Sàrl	Ch. des Cibleries 2, CP 300, 1896 Vouvry Tel. 024 482 61 61, Fax 024 482 61 69
curaden dentaldepot	Curaden AG Dentaldepot	Riedstrasse 12, 8953 Dietikon Tel. 041 319 45 00, Fax 041 319 45 90
dema dent	dema dent AG	Furtbachstrasse 16, 8107 Buchs Tel. 044 838 65 65, Fax 044 838 65 66
Flexdental	Flexdental Services SA	Route de la Corniche 1, 1066 Epalinges Tel. 0848 336 825, Fax 021 907 67 02
JOR DI Röntgentechnik	Jordi Röntgentechnik AG	Dammstrasse 70, 4142 Münchenstein Tel. 061 417 93 93, Fax 061 417 93 94
KALADENT	Kaladent AG	Schachenstrasse 2, 9016 St. Gallen Tel. 071 282 80 80, Fax 071 282 80 81
LOMETRAL Die Zahnarztausstatter.	Lometral AG	Binzenholzstrasse 20, 5704 Egliswil Tel. 062 775 05 05, Fax 062 775 33 07
<b>//O/</b> ADENT	Novadent AG	Sägereistrasse 17, 8152 Glattbrugg Tel. 044 880 20 20, Fax 044 811 04 40
Smart Dentist Ich kann auch sol	Smart Dentist AG	Verenastrasse 4b, 8832 Wollerau Tel. 044 726 20 20, Fax 044 726 20 25

Printing date 24.11.2022 Version number 5 Revision: 04.03.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Gloss and hardening agent for plasters

· Article number: 550 0000 1, 550 0000 2

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

· Application of the substance / the mixture: Liquid for coating and hardening gypsum surfaces.

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

bredent GmbH & Co.KG Weißenhorner Straße 2

89250 Senden

Tel: +49 (0) 7309/872-0 Fax: +49 (0) 7309/872-24

· Further information obtainable from:

R & D

e-mail: R.D@bredent.com

· 1.4 Emergency telephone number: (001) 352 323 3500

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling:

acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 2)

GB ·



Printing date 24.11.2022 Version number 5 Revision: 04.03.2022

Trade name: Gloss and hardening agent for plasters

(Contd. of page 1)

· Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Solvent mixture with additives

· Dangerous components:		
	acetone	50-100%
EINECS: 200-662-2	<ul> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	
CAS: 64-17-5	Ethanol	1-5%
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

GB



Printing date 24.11.2022 Version number 5 Revision: 04.03.2022

Trade name: Gloss and hardening agent for plasters

(Contd. of page 2)

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

#### 64-17-5 Ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

GB



Printing date 24.11.2022 Version number 5 Revision: 04.03.2022

Trade name: Gloss and hardening agent for plasters

(Contd. of page 3)

· Penetration time of glove material

The penetration time has to be at least 240 minutes (Permeation according to EN 374 Part 3: Level 5). The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
Odour: Characteristic

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 55 °C

· Flash point:	-19 °C
· Ignition temperature:	180 °C

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 2.6 Vol %

 Upper:
 13.0 Vol %

 • Vapour pressure at 20 °C:
 233 hPa

• **Density at 20 °C:** 0.85 g/cm<sup>3</sup>

0.00 8

· Solubility in / Miscibility with

water: Fully miscible.

• Viscosity:

viscosity.

Dynamic:Not determined.Kinematic:Not determined.

· Solvent content:

Organic solvents:92.4 %VOC (EC)> 90 %Solids content:7.5 %

• 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 5)



Printing date 24.11.2022 Version number 5 Revision: 04.03.2022

Trade name: Gloss and hardening agent for plasters

(Contd. of page 4)

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

#### 67-64-1 acetone

Oral LD50 5800 mg/kg (rat)
Dermal LD50 20000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- $\cdot \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

CD.

(Contd. on page 6)



Printing date 24.11.2022 Version number 5 Revision: 04.03.2022

Trade name: Gloss and hardening agent for plasters

(Contd. of page 5)

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR	1993 FLAMMABLE LIQUID, N.O.S. (ACETONE ETHANOL (ETHYL ALCOHOL)), special provision 640D
IMDG	FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHANO (ETHYL ALCOHOL))
IATA	FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHANOL)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids.
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33 F. F. C. F.
EMS Number: Stowage Category	F-E, <u>S-E</u> B
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	<b>f</b> Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml  Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL .
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (ACETONE
	ETHANOL (ETHYL ALCOHOL)), special provision 640L 3, II

## SECTION 15: Regulatory information

- $\cdot \textit{15.1 Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture} \\$
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms GHS02, GHS07

(Contd. on page 7)



Printing date 24.11.2022 Version number 5 Revision: 04.03.2022

Trade name: Gloss and hardening agent for plasters

(Contd. of page 6)

· Signal word Danger

· Hazard-determining components of labelling:

acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: R & D
- · Contact: R & D
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

bredent

GB