

## safety data sheet

### to product

### Separating agent for ceramics

### 1. Identification of the substance / preparation and company

#### **Emergency number:**

Tox Info Suisse, Freiestrasse 16, 8032 Zürich; Tox-Info Suisse: 145 (24h-operation); info@toxinfo.ch; **In case of emergency: Tel. 145**; (abroad: +41 44 251 51 51); information: +41 44 251 66 66

### **Company name:**

abcdental products a services	abc dental ag	Gaswerkstrasse 6, 8952 Schlieren Tel. 044 755 51 00, Fax 044 755 51 01
C NDOR  A MHENRY SCHEIN* COMPANY	Condor Dental Research CO Sàrl	Ch. des Cibleries 2, CP 300, 1896 Vouvry Tel. 024 482 61 61, Fax 024 482 61 69
curaden dentaldepot	Curaden AG Dentaldepot	Riedstrasse 12, 8953 Dietikon Tel. 041 319 45 00, Fax 041 319 45 90
dema dent	dema dent AG	Furtbachstrasse 16, 8107 Buchs Tel. 044 838 65 65, Fax 044 838 65 66
Flexdental	Flexdental Services SA	Route de la Corniche 1, 1066 Epalinges Tel. 0848 336 825, Fax 021 907 67 02
JORDI Röntgentechnik	Jordi Röntgentechnik AG	Dammstrasse 70, 4142 Münchenstein Tel. 061 417 93 93, Fax 061 417 93 94
KALADENT	Kaladent AG	Schachenstrasse 2, 9016 St. Gallen Tel. 071 282 80 80, Fax 071 282 80 81
LOMETRAL Die Zahnarztausstatter.	Lometral AG	Binzenholzstrasse 20, 5704 Egliswil Tel. 062 775 05 05, Fax 062 775 33 07
<b>//O/</b> ADENT	Novadent AG	Sägereistrasse 17, 8152 Glattbrugg Tel. 044 880 20 20, Fax 044 811 04 40
Smart Dentist Ich kann auch sol	Smart Dentist AG	Verenastrasse 4b, 8832 Wollerau Tel. 044 726 20 20, Fax 044 726 20 25

Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Separating agent for ceramics

· Article number: 540 0070 3

· 1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

· Application of the substance / the mixture: Isolating ceramic against plaster.

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: bredent GmbH & Co.KG

Weißenhorner Straße 2

89250 Senden

*Tel:* +49 (0) 7309/872-0 *Fax:* +49 (0) 7309/872-24

· Further information obtainable from:

R & D

e-mail: R.D@bredent.com

· 1.4 Emergency telephone number: (001) 352 323 3500

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS08
- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (Erdöl), mit Wasserstoff behandelt, leichte

· Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

*P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.* 

*P331* Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 2)

- GB



Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

Trade name: Separating agent for ceramics

· vPvB: Not applicable.

(Contd. of page 1)

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

Naphtha (petroleum), hydrotreated light

10-25%

- 🔖 Flam. Liq. 2, H225
- **♦** Asp. Tox. 1, H304
- Aquatic Chronic 2, H411
- Skin Irrit. 2, H315; STOT SE 3, H336
- · Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 3)

-GB



Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

Trade name: Separating agent for ceramics

(Contd. of page 2)

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

#### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

-GB



Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

Trade name: Separating agent for ceramics

(Contd. of page 3)

#### · Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0.4$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6). The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and cl General Information	hemical properties
· Appearance: Form:	Fluid
rorm: Colour:	Colourless
· Odour:	Characteristic
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	< 20 °C
· Ignition temperature:	250 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.8 Vol %
Upper:	7.7 Vol %
· Vapour pressure:	Not determined.
Density:	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Viscosity: Kinematic:	Not determined.
· Solvent content: Organic solvents:	0.0 %
9.2 Other information	No further relevant information available.

GB

(Contd. on page 5)



Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

Trade name: Separating agent for ceramics

(Contd. of page 4)

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification	ı:
--	----

#### Naphtha (petroleum), hydrotreated light

Oral	LD50	>2000 mg/kg (rat)
		>2000 mg/kg (rabbit)
Inhalative	LC50/1h	>5 mg/L (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

-GB

(Contd. on page 6)



Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

Trade name: Separating agent for ceramics

(Contd. of page 5)

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1268
14.2 UN proper shipping name ADR	1268 PETROLEUM DISTILLATES, N.O.S., spec provision 640D
IMDG, IATA	PETROLEUM DISTILLATES, N.O.S.
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
<b>1</b>	
Class Label	3 Flammable liquids.
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids. 33
EMS Number:	F-E,S-E
14.7 Transport in bulk according to Annex II o	f
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L Code: E2
Excepted quantities (EQ)	Coae: E2  Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml  Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL Coder F2
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml  Maximum net quantity per outer packaging: 500 ml

bredent

Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

Trade name: Separating agent for ceramics

(Contd. of page 6)

· UN "Model Regulation": UN1268, PETROLEUM DISTILLATES, N.O.S., special

provision 640D, 3, II

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS08
- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (Erdöl), mit Wasserstoff behandelt, leichte

· Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P233 Keep container tightly closed.* 

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

*P331* Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R & D
- · Contact: R & D
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

(Contd. on page 8)





Page 8/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.11.2022 Version number 5 Revision: 12.08.2021

Trade name: Separating agent for ceramics

(Contd. of page 7)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· \* Data compared to the previous version altered.

