

safety data sheet

to product

Lucitone HIPA Liquid

1. Identification of the substance / preparation and company

Emergency number:

Tox Info Suisse, Freiestrasse 16, 8032 Zürich; Tox-Info Suisse: 145 (24h-operation); info@toxinfo.ch;
In case of emergency: Tel. 145; (abroad: +41 44 251 51 51); information: +41 44 251 66 66

Company name:



abc dental ag

Gaswerkstrasse 6, 8952 Schlieren
Tel. 044 755 51 00, Fax 044 755 51 01



Condor Dental Research CO Sàrl

Ch. des Cibleries 2, CP 300, 1896 Vouvry
Tel. 024 482 61 61, Fax 024 482 61 69



Curaden AG Dentaldepot

Riedstrasse 12, 8953 Dietikon
Tel. 041 319 45 00, Fax 041 319 45 90



dema dent AG

Furtbachstrasse 16, 8107 Buchs
Tel. 044 838 65 65, Fax 044 838 65 66



Flexdental Services SA

Route de la Corniche 1, 1066 Epalinges
Tel. 0848 336 825, Fax 021 907 67 02



Jordi Röntgentechnik AG

Dammstrasse 70, 4142 Münchenstein
Tel. 061 417 93 93, Fax 061 417 93 94



Kaladent AG

Schachenstrasse 2, 9016 St. Gallen
Tel. 071 282 80 80, Fax 071 282 80 81



Lometral AG

Binzenholzstrasse 20, 5704 Egliswil
Tel. 062 775 05 05, Fax 062 775 33 07



Novadent AG

Sägereistrasse 17, 8152 Glattbrugg
Tel. 044 880 20 20, Fax 044 811 04 40



Smart Dentist AG

Verenastrasse 4b, 8832 Wollerau
Tel. 044 726 20 20, Fax 044 726 20 25

SAFETY DATA SHEET (EC 1907/2006)**Lucitone HIPA Liquid**

Version: **1.4 / GB**
Revision date: **20.11.2020**
Issue date: **09.10.2015**
replaces version: **1.3**
Page: **1 / 11**

Material no.
Specification **182802**
VA-Nr **01906948**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name Lucitone HIPA Liquid
REACH Registration No.: if available listed in Chapter. 3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant applications identified For dental use only.

1.3. Details of the supplier of the safety data sheet

Company DeguDent GmbH
Postfach 1364
D-63403 Hanau
Telephone +49 (0)6181/59-5576
Telefax +49 (0)6181/59-5879
Email address SDB.Degudent-DE@dentsplysirona.com

1.4. Emergency telephone number

Emergency information +49 (0)6181/59-50 (This telephone number is available during office hours only.)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids	Category 2	H225
Skin corrosion/irritation	Category 2	H315
Skin Sensitisation	Category 1	H317
Specific Target Organ Toxicity - Single exposure (inhalation)	Category 3	H335

2.2. Label elements**Labelling as per (EU) 1272/2008**

Statutory basis EU-CLP as per Regulation (EU) No. 1272/2008, Annex VI

hazard-defining component(s) (GHS)

- methyl methacrylate
- Hazard pictograms



SAFETY DATA SHEET (EC 1907/2006)

Lucitone HIPA Liquid

Version: 1.4 / GB
Revision date: 20.11.2020
Issue date: 09.10.2015
replaces version: 1.3
Page: 2 / 11

Material no.
Specification 182802
VA-Nr 01906948



Signal word	Danger
Hazard statement	H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation.
Precautionary statement: Prevention	P280 - Wear protective gloves/ eye protection/ face protection. P260 - Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautionary statement: Storage	P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Precautionary statement: Disposal	P501 - Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

When heated, formation of explosive vapour/air mixtures., Danger of bursting of closed systems to vigorous exothermic polymerization. Avoid uncontrolled polymerization.
A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

SECTION 3: Composition/information on ingredients

Chemical nature

The mixture contains:, acrylic resin based on: methyl methacrylate

3.1. Substances

-

3.2. Mixtures

Information on ingredients / Hazardous components as per EU-CLP Regulation (EC) No. 1272/2008

• methyl methacrylate		70% - 90%	
CAS-No.	80-62-6	EC-No.	201-297-1
Flammable liquids		Category 2	H225
Skin corrosion/irritation		Category 2	H315
Skin Sensitisation		Category 1	H317
Specific Target Organ Toxicity - Single exposure (inhalation)		Category 3	H335
• methacrylic acid ester		5% - 15%	
Skin Sensitisation		Category 1B	H317
Chronic aquatic toxicity		Category 3	H412

Texts of H phrases, see in Chapter 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Take off all contaminated clothing immediately.

Inhalation

Move victims into fresh air.
Obtain medical attention.

Skin contact

Wash off immediately with soap and plenty of water.
Obtain medical attention.

SAFETY DATA SHEET (EC 1907/2006)

Lucitone HIPA Liquid

Version: **1.4 / GB**
Revision date: **20.11.2020**
Issue date: 09.10.2015
replaces version: 1.3
Page: **3 / 11**

Material no.
Specification **182802**
VA-Nr **01906948**



Eye contact

With eye held open, thoroughly rinse immediately with plenty of water for at least 5 minutes. Consult an ophthalmologist.

Ingestion

Do NOT induce vomiting.
Have the mouth rinsed with water.
Have patient drink plenty of water in small sips.
Obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

If skin sensitisation has developed and a causal relationship has been confirmed, further exposure should not be allowed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: quenching powder
Carbon dioxide (CO₂)
Alcohol-resistant foam

Unsuitable extinguishing media: Water

5.2. Special hazards arising from the substance or mixture

In case of combustion or decomposition of the product, the fumes produced lead to irritations or inflammations of the respiratory tract.
When heated, formation of explosive vapour/air mixtures.

5.3. Advice for firefighters

In case of fire cool containers or take them to a safe place.
Use water spray to cool unopened containers.
In the case of fire, wear respiratory protective equipment independent of surrounding air and chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep unauthorized persons away.
Wear personal protective equipment.
Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

Prevent substance from entering soil, natural bodies of water and sewer systems., Avoid penetration into drainage system or in rooms situated at a lower level because of danger of explosion.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition.
Absorb with liquid-binding material, e.g. inert absorbent, sand, universal binding agents.
Pick up mechanically with a suitable device and collect in a suitable container.

Additional advice

Ensure explosion proofness. Dispose of contaminated material as a waste in a correct manner.

6.4. Reference to other sections

Wear personal protective equipment; see section 8.
Disposal considerations; see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

SAFETY DATA SHEET (EC 1907/2006)

Lucitone HIPA Liquid

Version: 1.4 / GB
Revision date: 20.11.2020
Issue date: 09.10.2015
replaces version: 1.3
Page: 4 / 11

Material no.
Specification 182802
VA-Nr 01906948



Always close container tightly after removal of product.
Avoid light effect heat sun rays.
Vapors are heavier than air.
Only fill up to 90 % of the container as air is required to stabilize.

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
product is highly flammable.
Vapours are heavier than air and may spread along floors.
Formation of flammable or explosive vapour/air mixtures possible. Danger of explosion
Explosion-proof installations required.
Take precautionary measures against static discharges.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place.
Ensure there is good room ventilation.

German storage class

3 - Flammable liquids

7.3. Specific end use(s)

We are unaware of any specific end uses which go beyond the data reported in Section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

• methyl methacrylate			
CAS-No.	80-62-6	EC-No.	201-297-1
Control parameters	100 ppm 416 mg/m ³		Short Term Exposure Limit (STEL):(EH40 WEL)
Control parameters	50 ppm 208 mg/m ³		Time Weighted Average (TWA):(EH40 WEL)

8.2. Exposure controls

Engineering measures

Ensure suitable suction/aeration at the work place and with operational machinery.

Personal protective equipment

Respiratory protection

If workplace exposure limit is exceeded apply Respirator with brown A-type filter.

Hand protection

Wear protective gloves made of the following materials: solvent-resistant material.

Glove material butyl-rubber

Material thickness 0.5 mm

Break through time 60 min

Method Source: GESTIS substance database (hazardous substance information system of commercial professional associations)

The suitability for a specific workplace should be discussed with the producers of the protective gloves.,
The exact break through time can be obtained from the protective glove producer and this has to be observed.

Preventive skin protection, Use barrier cream regularly.

Eye/face protection

goggles

Skin and body protection

Immediately change moistened and saturated work clothes., Apply adequate skin protection agents before handling the product. Assure skin cleaning and skin care after work. Preventive skin protection is recommended.

SAFETY DATA SHEET (EC 1907/2006)**Lucitone HIPA Liquid**

Version: **1.4 / GB**
Revision date: **20.11.2020**
Issue date: **09.10.2015**
replaces version: **1.3**
Page: **5 / 11**

Material no.
Specification **182802**
VA-Nr **01906948**

**Hygiene measures**

Do not eat, drink, smoke, or sniff while at work. Wash your hands and/or face before breaks and before termination of work., If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used., Avoid contact with skin and eyes., After contact with skin, wash immediately with plenty of water., If there is the possibility of skin/eye contact, the indicated hand/eye/body protection should be used.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance

Form liquid
Colour colourless

Odour ester-like

Odour threshold: no data available

pH not applicable

Melting point/range -48.2 °C
tested substance:
methyl methacrylate

Boiling point/range 100.3 °C (1013 hPa)
Method: DIN 51 751
tested substance:
methyl methacrylate

Flash point 10 °C
Method: DIN 51 755
tested substance:
methyl methacrylate

Evaporation rate no data available

Flammability (solid, gas) no data available

Lower explosion limit 2.1 %(V)
tested substance:
methyl methacrylate

Upper explosion limit 12.5 %(V)
tested substance:
methyl methacrylate

Vapour pressure 38.7 hPa (20 °C)
tested substance:
methyl methacrylate

Density 0.94 g/cm³ (20 °C)
Method: DIN 51757
tested substance:
methyl methacrylate

Relative density no data available

Water solubility 15.9 g/l (20 °C)

SAFETY DATA SHEET (EC 1907/2006)**Lucitone HIPA Liquid**

Version:	1.4 / GB	Material no.	
Revision date:	20.11.2020	Specification	182802
Issue date:	09.10.2015	VA-Nr	01906948
replaces version:	1.3		
Page:	6 / 11		



	tested substance: methyl methacrylate
Partition coefficient: n-octanol/water	POW: 1.38 tested substance: methyl methacrylate
Autoinflammability	Not capable of spontaneous combustion or heating.
Thermal decomposition	no data available
Viscosity, dynamic	0.63 mPa.s (20 °C) Method: Brookfield method tested substance: methyl methacrylate
Viscosity, kinematic	no data available
Explosiveness	Vapours can form explosive mixtures with air.
Oxidizing properties	no data available
9.2. Other information	
Ignition temperature	430 °C Method: DIN 51 794 tested substance:, methyl methacrylate
Other information	No further physicochemical data were determined.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours may form explosive mixture with air.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Danger of bursting of closed systems to vigorous exothermic polymerization. Avoid uncontrolled polymerization.

10.4. Conditions to avoid

Avoid exposure to light /sunlight, Protect from heat sources of ignition.

10.5. Incompatible materials

Product polymerizes on contact with radical generating substances such as peroxides, azo compounds, heavy metal compounds, solutions.

10.6. Hazardous decomposition products

Heating can release vapours which can be ignited.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute oral toxicity	LD50 Rat: > 5000 mg/kg
	Method: OECD Test Guideline 401
	Test substance: methyl methacrylate
	literature

SAFETY DATA SHEET (EC 1907/2006)**Lucitone HIPA Liquid**

Version: **1.4 / GB**
Revision date: **20.11.2020**
Issue date: **09.10.2015**
replaces version: **1.3**
Page: **7 / 11**

Material no.
Specification **182802**
VA-Nr **01906948**



Acute inhalation toxicity	LC50 Rat: 29.8 mg/l / 4 h Test substance: methyl methacrylate (literature value)
Acute dermal toxicity	LD50 Rabbit: > 5000 mg/kg Test substance: methyl methacrylate literature
Skin irritation	irritating Test substance: methyl methacrylate literature
Eye irritation	slightly irritating Test substance: methyl methacrylate literature
Sensitization	May cause sensitisation by skin contact. Test substance: methyl methacrylate literature
Repeated dose toxicity	inhalative Rat Testing period: 2 Jahre NOAEL: 25 mg/kg target organ/effect: irritative effects, skin linings Test substance: methyl methacrylate literature Oral Rat Testing period: 2 Jahre NOAEL: 2000 mg/kg Test substance: methyl methacrylate drinking water analysis, no therapy-related results, literature
Assessment of STOT single exposure	no data available
Assessment of STOT repeat exposure	no data available
Risk of aspiration toxicity	no data available
Gentoxicity in vitro	positive and negative Test substance: methyl methacrylate literature
Gentoxicity in vivo	no evidence of mutagenic effects Test substance: methyl methacrylate literature
Mutagenicity assessment	in vivo: no evidence of mutagenic effects
carcinogenicity assessment	no evidence that cancer may be caused, literature., tested substance:, methyl methacrylate
Toxicity to reproduction	no data available
teratogenicity assessment	no evidence of teratogenic properties, tested substance:, methyl methacrylate

SECTION 12: Ecological information

SAFETY DATA SHEET (EC 1907/2006)

Lucitone HIPA Liquid

Version: **1.4 / GB**
Revision date: **20.11.2020**
Issue date: **09.10.2015**
replaces version: **1.3**
Page: **8 / 11**

Material no.
Specification **182802**
VA-Nr **01906948**



12.1. Toxicity

Toxicity to fish

LC50 *Lepomis macrochirus*: 191 mg/l / 96 h

Test substance: methyl methacrylate
literature

Oncorhynchus mykiss: > 79 mg/l / 96 h

Test substance: methyl methacrylate
Method: OECD 203
literature

Toxicity in aquatic invertebrates

EC50 *Daphnia magna*: 68 mg/l / 48 h

Test substance: methyl methacrylate
Method: OECD 202
(literature value)

EC50 *Daphnia magna*: 49 mg/l / 21 d

Test substance: methyl methacrylate
Method: OECD 202 part 2
(literature value)

Toxicity to algae

EC50 *Selenastrum capricornutum*: 170 mg/l / 96 h

Test substance: methyl methacrylate
Method: OECD 201
literature

Toxicity to bacteria

EC0 *Pseudomonas putida*: 100 mg/l

Test substance: methyl methacrylate
literature

12.2. Persistence and degradability

Biodegradability

Exposure time: 14 Tage

Result: 94 % Readily biodegradable.

Test substance: methyl methacrylate

Method: OECD 301 C

12.3. Bioaccumulative potential

Bioaccumulation

Significant bioaccumulation need not be expected.

12.4. Mobility in soil

Mobility

If the product penetrates the soil it will become mobile and might pollute the groundwater.

12.5. Results of PBT and vPvB assessment

A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

12.6. Other adverse effects

Further Information

Introduction into soil, natural water bodies or sewerage must be prevented.

SAFETY DATA SHEET (EC 1907/2006)**Lucitone HIPA Liquid**

Version: **1.4 / GB**
Revision date: **20.11.2020**
Issue date: **09.10.2015**
replaces version: **1.3**
Page: **9 / 11**

Material no.
Specification **182802**
VA-Nr **01906948**

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Product**

Disposal according to local authority regulations.

Uncleaned packaging

Disposal according to local authority regulations.

SECTION 14: Transport information**Transport on land (ADR/RID/GGVSEB)**

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
ADR: Tunnel Restriction Code: (D/E)
ADR: Measures as 2.2.3.2.2 ADR/RID/ADN have been applied., Observe listed materials regulation §35, paragraph 1 GGVSEB
RID: Measures as 2.2.3.2.2 ADR/RID/ADN have been applied.

Inland waterway transport (ADN/GGVSEB (Germany))

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
Measures as 2.2.3.2.2 ADR/RID/ADN have been applied.

Air transport ICAO-TI/IATA-DGR

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: Methyl methacrylate monomer, stabilized solution
14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
IATA-C: FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity-Regulation!
IATA-P: FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity-Regulation!

Sea transport IMDG-Code/GGVSee (Germany)

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
EmS: F-E,S-D
Clear of living quarters., FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity-Regulation!

- 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

SAFETY DATA SHEET (EC 1907/2006)**Lucitone HIPA Liquid**

Version: **1.4 / GB**
Revision date: **20.11.2020**
Issue date: **09.10.2015**
replaces version: **1.3**
Page: **10 / 11**

Material no.
Specification **182802**
VA-Nr **01906948**



for transportapproval see regulatory information

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National legislation**

employment restriction

Note employment restrictions for pregnant and lactating women., Note employment restrictions for minors.

15.2. Chemical safety assessment

Chemical safety assessment

No Chemical Safety Report as per Articles 2(8), 2(9) or 14 of the REACH Regulation is required for this product.

SECTION 16: Other information**Classification and applied procedure to derive the classification of mixtures according to EU Regulation (EC) No. 1272/2008 (CLP)**

Classification	Classification procedure
Flam. Liq., 2 , H225 Skin Corr./Skin Irrit., 2 , H315 Skin.sens., 1 , H317 STOT SE, 3 , H335	

Relevant H phrases from chapter 3

H225 : Highly flammable liquid and vapour.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H335 : May cause respiratory irritation.
H412 : Harmful to aquatic life with long lasting effects.

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Legend

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ASTM American Society for Testing and Materials
ATP Adaptation to Technical Progress
BCF Bioconcentration factor
BetrSichV German Ordinance on Industrial Safety and Health
c.c. closed cup
CAS Chemical Abstract Services
CESIO European Committee of Organic Surfactants and their Intermediates
ChemG German Chemicals Act

SAFETY DATA SHEET (EC 1907/2006)**Lucitone HIPA Liquid**

Version:	1.4 / GB	Material no.	
Revision date:	20.11.2020	Specification	182802
Issue date:	09.10.2015	VA-Nr	01906948
replaces version:	1.3		
Page:	11 / 11		



CMR	carcinogenic-mutagenic-toxic for reproduction
DIN	German Institute for Standardization
DMEL	Derived minimum effect level
DNEL	Derived no effect level
EINECS	European Inventory of Existing Commercial Chemical Substances
EC50	half maximal effective concentration
GefStoffV	German Ordinance on Hazardous Substances
GGVSEB	German ordinance for road, rail and inland waterway transportation of dangerous goods
GGVSee	German ordinance for sea transportation of dangerous goods
GLP	Good Laboratory Practice
GMO	Genetic Modified Organism
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
ISO	International Organization For Standardization
LOAEL	Lowest observed adverse effect level
LOEL	Lowest observed effect level
NOAEL	No observed adverse effect level
NOEC	no observed effect concentration
NOEL	no observed effect level
o. c.	open cup
OECD	Organisation for Economic Cooperation and Development
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative, toxic
PEC	Predicted effect concentration
PNEC	Predicted no effect concentration
REACH	REACH registration
RID	Convention concerning International Carriage by Rail
STOT	Specific Target Organ Toxicity
SVHC	Substances of Very High Concern
TA	Technical Instructions
TPR	Third Party Representative (Art. 4)
TRGS	Technical Rules for Hazardous Substances
VCi	German chemical industry association
vPvB	very persistent, very bioaccumulative
VOC	volatile organic compounds
VwVwS	German Administrative Regulation on the Classification of Substances Hazardous to Waters into Water Hazard Classes
WGK	Water Hazard Class
WHO	World Health Organization