

safety data sheet

to product

GC Pattern Resin LS Liquid

1. Identification of the substance / preparation and company

Emergency number:

Tox Info Suisse, Freiestrasse 16, 8032 Zürich; Tox-Info Suisse: 145 (24h-operation); info@toxinfo.ch; **In case of emergency: Tel. 145**; (abroad: +41 44 251 51 51); information: +41 44 251 66 66

Company name:

abcdental absolutely best choice	abc dental ag	Gaswerkstrasse 6, 8952 Schlieren Tel. 044 755 51 00, Fax 044 755 51 01
C NDOR A MHENRY SCHEIN' COMPANY	Condor Dental Research CO Sàrl	Ch. des Cibleries 2, CP 300, 1896 Vouvry Tel. 024 482 61 61, Fax 024 482 61 69
curaden dentaldepot	Curaden AG Dentaldepot	Riedstrasse 12, 8953 Dietikon Tel. 041 319 45 00, Fax 041 319 45 90
dema dent	dema dent AG	Furtbachstrasse 16, 8107 Buchs Tel. 044 838 65 65, Fax 044 838 65 66
Flexdental	Flexdental Services SA	Route de la Corniche 1, 1066 Epalinges Tel. 0848 336 825, Fax 021 907 67 02
JORDI Röntgentechnik	Jordi Röntgentechnik AG	Dammstrasse 70, 4142 Münchenstein Tel. 061 417 93 93, Fax 061 417 93 94
KALADENT	Kaladent AG	Schachenstrasse 2, 9016 St. Gallen Tel. 071 282 80 80, Fax 071 282 80 81
LOMETRAL Die Zahnarztausstatter.	Lometral AG	Binzenholzstrasse 20, 5704 Egliswil Tel. 062 775 05 05, Fax 062 775 33 07
//O/A DENT	Novadent AG	Sägereistrasse 17, 8152 Glattbrugg Tel. 044 880 20 20, Fax 044 811 04 40
Smart		

Smart Dentist AG

Verenastrasse 4b, 8832 Wollerau

Tel. 044 726 20 20, Fax 044 726 20 25



Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GC Pattern Resin LS Liquid
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00

Fax + 32/(0)16/40.26.84

msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

· Signal word Danger

(Contd. on page 2)

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 1)

· Hazard-determining components of labelling:

Methyl methacrylate ethyl methacrylate

2-(2H-benzotriazol-2-yl)-p-cresol

Ethyleneglycol dimethacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 80-62-6	Methyl methacrylate	50-<75%
EINECS: 201-297-1 Index number: 607-035-00-6	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 6976-93-8	2-Methoxyethyl methacrylate	10-<25%
EINECS: 230-241-9	Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 97-63-2	ethyl methacrylate	5-<10%
EINECS: 202-597-5 Index number: 607-071-00-2	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	1-<2.5%
EINECS: 202-805-4 Index number: 612-056-00-9	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 3, H412	

(Contd. on page 3)

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

	(Co	ontd. of page 2)
CAS: 2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol	0.5-<1%
EINECS: 219-470-5	Acute Tox. 2, H330; Aquatic Chronic 1, H410; Skin Sens. 1, H317	
CAS: 97-90-5	Ethyleneglycol dimethacrylate	0.5-<1%
EINECS: 202-617-2	Skin Sens. 1, H317; STOT SE 3, H335	1
Index number: 607-114-00-5		

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Do not use mouth to mouth or mouth to nose resuscitation.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB ·

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

Prevent seepage into sewage system, workpits and cellars.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 4)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:			
80-62	80-62-6 Methyl methacrylate		
WEL	Short-term value: 416 mg/m³, 100 ppm		
	Long-term value: 208 mg/m³, 50 ppm		

· DNELs

80-62-6 M	80-62-6 Methyl methacrylate		
Dermal	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)	
Inhalative	DNEL inhalation	208 mg/m3 (air) (worker, l. te., syst.)	

· PNECs

99-97-8 N,N-dimethyl-p-toluidine

PNEC Aqua | 152.59 µg/L (freshwater)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Suitable respiratory protective device recommended.

· Protection of hands:



Protective gloves

· Material of gloves

e.g. KCL Butoject 897

Butyl rubber, BR

Recommended thickness of the material: $\geq 0.29 \text{ mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 2).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


(Contd. on page 6)

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 5)

· Eye protection:



SECTION 9: Physical and chem	* *
9.1 Information on basic physical and o	chemical properties
General Information	
Appearance:	I:: I
Form: Colour:	Liquid Clear
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
Flash point:	10 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Vapour pressure:	Not determined.
Density at 20 °C:	0.95 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
VOC (EC)	0.0 g/l

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATEmix (Oral) = 5284 mg/kg

ATEmix (dermal) > 4740 mg/kg

ATEmix (inhal.) = 15 mg/l

*	, , ,		
80-62-6 M	80-62-6 Methyl methacrylate		
Oral	LD50	6000 mg/kg (rabbit)	
Dermal	LD50	>5000 mg/kg (rab)	
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))	
97-63-2 eti	hyl methac	rylate	
Oral	LD50	13424 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	55 mg/l (rat (f+m))	
99-97-8 N,	N-dimethy	rl-p-toluidine	
Oral	LD50	1650 mg/kg (rat (f+m))	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	1.4 mg/l (rat (f+m))	
2440-22-4	2440-22-4 2-(2H-benzotriazol-2-yl)-p-cresol		
Oral	LD50	10000 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	0.59 mg/l (rat (f+m))	
97-90-5 Ethyleneglycol dimethacrylate			
Oral	LD50	8700 mg/kg (rat (f+m))	
Dermal	LD50	>2000 mg/kg (rat (f+m))	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Repeated dose toxicity No further relevant information available.

(Contd. on page 8)

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 7)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 No further relevant information available.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

99-97-8 N,N-dimethyl-p-toluidine

LC50/96h 46 mg/L (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	· European waste catalogue		
18 00 00 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RE- kitchen and restaurant wastes not arising from immediate health care)		WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care)	
18 01 00 wastes from natal care, diagnosis, treatment or prevention of disease in humans 18 01 06* chemicals consisting of or containing dangerous substances		wastes from natal care, diagnosis, treatment or prevention of disease in humans	
		chemicals consisting of or containing dangerous substances	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

GB

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 8)

SECTION 14: Transport informa	tion
14.1 UN-Number	
ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name	
ADR	1247 METHYL METHACRYLATE MONOMER, STABILIZED
IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label 	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	339
EMS Number:	F- E , S - D
Stowage Category	B
Stowage Code	SW2 Clear of living quarters.
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
T.,	Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
	טוע
IMDG	17
Limited quantities (LQ)	1L

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

	(Contd. of page 9)
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, , II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 2: Acute toxicity – Category 2

(Contd. on page 11)

Printing date 02.08.2018 Version number 7 Revision: 21.06.2017

Trade name: GC Pattern Resin LS Liquid

(Contd. of page 10)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

GB ·