

safety data sheet

to product

Stabiloplast Accelerator #448 0002

1. Identification of the substance / preparation and company

Emergency number:

Tox Info Suisse, Freiestrasse 16, 8032 Zürich; Tox-Info Suisse: 145 (24h-operation); info@toxinfo.ch; **In case of emergency: Tel. 145**; (abroad: +41 44 251 51 51); information: +41 44 251 66 66

Company name:

abcdental products & services	abc dental ag	Gaswerkstrasse 6, 8952 Schlieren Tel. 044 755 51 00, Fax 044 755 51 01
C NDOR A MHENRY SCHEIN* COMPANY	Condor Dental Research CO Sàrl	Ch. des Cibleries 2, CP 300, 1896 Vouvry Tel. 024 482 61 61, Fax 024 482 61 69
curaden dentaldepot	Curaden AG Dentaldepot	Riedstrasse 12, 8953 Dietikon Tel. 041 319 45 00, Fax 041 319 45 90
dema dent	dema dent AG	Furtbachstrasse 16, 8107 Buchs Tel. 044 838 65 65, Fax 044 838 65 66
Flexdental	Flexdental Services SA	Route de la Corniche 1, 1066 Epalinges Tel. 0848 336 825, Fax 021 907 67 02
JORDI Röntgentechnik	Jordi Röntgentechnik AG	Dammstrasse 70, 4142 Münchenstein Tel. 061 417 93 93, Fax 061 417 93 94
KALADENT	Kaladent AG	Schachenstrasse 2, 9016 St. Gallen Tel. 071 282 80 80, Fax 071 282 80 81
LOMETRAL Die Zahnarztausstatter.	Lometral AG	Binzenholzstrasse 20, 5704 Egliswil Tel. 062 775 05 05, Fax 062 775 33 07
MOM DENT	Novadent AG	Sägereistrasse 17, 8152 Glattbrugg Tel. 044 880 20 20, Fax 044 811 04 40
Smart Dentist Ich kann auch so!	Smart Dentist AG	Verenastrasse 4b, 8832 Wollerau Tel. 044 726 20 20, Fax 044 726 20 25



according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Stabiloplast Accelerator 448 0002

Further trade names

contained in: 448 0004 Stabiloplast Set

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Polymerizationaccelerator

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Renfert GmbH
Street: Untere Giesswiesen 2
Place: D-78247 Hilzingen
Telephone: +49 7731 8208-0
e-mail: info@renfert.com
Contact person: Frau Andris

e-mail: silke.andris@renfert.com Internet: www.renfert.com

1.4. Emergency telephone number: IRL: 01 809 2566 (Healthcare Professionals) | GB: 0044 151 951 3317 (Health and

Safety Executive (HSE) Chemicals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetone

Signal word: Danger Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Do not breathe mist/vapours/spray.

P280 Wear protective gloves and eye/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





2.3. Other hazards





according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 2 of 8

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no

components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Polymerizationaccelerator

Hazardous components

CAS No	Chemical name	Chemical name					
	EC No	Index No	REACH No				
	Classification (Regulation (E	EC) No 1272/2008)					
67-64-1	64-1 acetone			> 80 %			
	200-662-2	606-001-00-8	01-2119471330-49				
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066						
99-97-8	N,N-dimethyl-p-toluidine	N,N-dimethyl-p-toluidine					
	202-805-4	612-056-00-9	01-2119956633-31				
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 3; H330 H311 H301 H373 H412						

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. Lim	c Conc. Limits, M-factors and ATE			
99-97-8	202-805-4	N,N-dimethyl-p-toluidine	< 1 % %		
	inhalation: LC50 = 1,4 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 139 mg/kg				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes.

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures



according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 3 of 8

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.

Avoid contact with eyes and skin.

Do not eat, drink or smoke when using this product.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Avoid breathing vapours.

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Please refer to our internet website for more information. www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift

8.2. Exposure controls





Appropriate engineering controls

Safe handling: see section 7

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.





according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 4 of 8

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: >= 240 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above

together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

Use only in well-ventilated areas.

Usually no personal respirative protection necessary.

Respiratory protection necessary at: insufficient ventilation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear Odour: characteristic Odour threshold: not determined

Test method

Melting point/freezing point: not determined 54 °C

Boiling point or initial boiling point and boiling

range:

Flammability: No data available Lower explosion limits: 2.5 * vol. % 13.0 * vol. % Upper explosion limits:

Flash point: - 18 °C DIN 51755 (cc) 535 * °C Literaturwert Auto-ignition temperature:

Decomposition temperature: not determined pH-Value: not applicable Viscosity / kinematic: not determined Water solubility: miscible Partition coefficient n-octanol/water: log Pow: - 0,24 * 246 * hPa Vapour pressure:

(at 20 °C)

Density (at 20 °C): 0,78 - 0,82 g/cm³ Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not explosive.

Vapours can form explosive mixtures with air.

Other safety characteristics

Solvent content: > 80 %

Further Information

* Data apply to the main component.

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. May form explosive peroxides.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 5 of 8

10.5. Incompatible materials

Violent reaction with: Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 14040,4 mg/kg; ATE (dermal) 30303,0 mg/kg; ATE (inhalation vapour) 141,41 mg/l; ATE (inhalation dust/mist) 5,051 mg/l

CAS No	Chemical name	Chemical name						
	Exposure route	Dose		Species	Source	Method		
99-97-8	N,N-dimethyl-p-toluidine							
	oral	LD50	139 mg/kg	Mouse	IUCLID			
	dermal	ATE	300 mg/kg					
	inhalation (4 h) vapour	LC50	1,4 mg/l	Rat	IUCLID			
	inhalation dust/mist	ATE	0,05 mg/l					

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity Dose [h] [d] Species Source Method					Method	
99-97-8	N,N-dimethyl-p-toluidine						
	Acute fish toxicity	LC50	46 mg/l		Pimephales promelas (fathead minnow)	IUCLID	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,24
99-97-8	N,N-dimethyl-p-toluidine	2,81



according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 6 of 8

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Send to a hazardous waste incinerator facility under observation of official regulations.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical

products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1090
14.2. UN proper shipping name:	ACETON
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



1111 4000

Marine transport (IMDG)

14.1. UN number or ID number: UN 1090

14.2. UN proper shipping name: ACETONE (ACETONE SOLUTIONS)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant: no

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 109014.2. UN proper shipping name:Acetone14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



14.5. Environmental hazards





according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 7 of 8

ENVIRONMENTALLY HAZARDOUS:

14.6. Special precautions for user

Further information: see section 6, 7, 8

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 100 % (780 g/l)

Additional information

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work

protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe employment restrictions for women of child-bearing age. 2 - obviously hazardous to water

Water hazard class (D):

Additional information

Regulation (EC) No. 2037/2000 concerning materials, which cause damage to the ozone layer; not applicable REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic

pollutants: not applicable

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of

dangerous chemicals: not applicable

SECTION 16: Other information

Changes

Abs. 2, 9, 11, 15 * Data changed compared with the previous version.

Abbreviations and acronyms

PBT: persistent and bioaccumulative and toxic vPvB: very persistent, very bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

ATE: Acute Toxicity Estimate LD50: lethal dose, 50% LC50: lethal concentration, 50%

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning

the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure			
Flam. Liq. 2; H225	On basis of test data			
Eye Irrit. 2; H319	Calculation method			
STOT SE 3; H336	Calculation method			

Re

3L 3, 11330	Calculation method					
elevant H and EUH statements (number and full text)						
H225 Highly fla	mmable liquid and vapour.					
H301 Toxic if sv	vallowed.					
H311 Toxic in c	contact with skin.					
H319 Causes s	erious eye irritation.					

H330 Fatal if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.





according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023 Product code: 4480002 Page 8 of 8

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)